

Product Data Sheet



AromaFresh 2.0 Therm

| Technical Data | |  |
|--|----------------------------------|---|
| Type | 1030-XX | |
| Power rating | 920-1080 [W] | |
| Voltage | 220-240 [V] | |
| Frequency | 50-60 [Hz] | |
| Weight | 3,963 [kg] *) | |
| Weight with packaging | 5,591 [kg] *) | |
| Height x Width x Depth | 463 x 268 x 269 [mm x mm x mm] | |
| Height x Width x Depth packaging | [mm x mm x mm] | |
| Water tank volume | 1,0 [l] | |
| Maximum amount of coffee | 8 [cups] / [l] | |
| Brewing time | 07:45 [mm:ss] (approx.) | |
| Finish brew coffee | 80°C-85°C [°C] (approx.) | |
| Warmkeeping temperature | 80°C-85°C [°C] (approx.) | |
| Automatic shut-off time | 20-60min [min] | |
| Filter size | 1x4 | |
| | | Available colours: |
| | | 1030-11 matt Black |
| | | 1030-12 matt Black Decor |
| | | *) Weight of -11 Version weight of -12 find below |
| | | 3,997 kg |
| | | 5,460 kg with packaging |
| Feature Details | | |
| Insulating jug | | |
| - stainless steel insulating jug, double wall, evacuated | | |
| - direct brewing lid | | |
| - jug lid with one hand operation for pouring | | |
| - new innovative jug lid, easy to remove and to place on the jug | | |
| Water tank | | |
| - water level indication for 2 to 8 cups | | |
| - transparent water tank | | |
| - removable water tank | | |
| - removable water tank lid | | |
| - water level visible from the front side | | |
| Filter | | |
| - swing filter holder with filter lock | | |
| - removable swing filter for easy cleaning | | |
| - removable filter | | |
| - removable filter in black colour | | |
| - break-proof | | |
| - drip stop | | |
| - dishwasher safe | | |
| - filter size 1x4 | | |
| Housing | | |
| - matt textured surface | | |
| Brewing system | | |
| - 1000W heating system | | |
| - well-balanced brewing temperature for coffee extraction | | |
| - two brewing modes: full power and reduced power, reduced power for 2 and 4 cup preparation | | |
| Grinder system | | |
| - integrated disk grinder | | |
| - various grind settings: fine, medium, coarse | | |
| - adjustable coffee intensity: 5 steps from mild to strong | | |
| - manual adjustment of grind quantity | | |
| - grind OFF function for using pre grounded coffee | | |
| - transparent bean container with removable lid | | |
| - detachable upper grind head for grinder cleaning | | |
| - cleanable ground coffee chute with enclosed cleaning brush | | |
| Calcification indication | | |
| - necessity to descale shown with red LED | | |
| Descaling program | | |

| | |
|---------------------------|---|
| | - CALC button to start descaling program |
| | - remaining time shown on display |
| | - CALC shown on display |
| | - decalcification process works with reduced power for good calc removal |
| Brewing end signal | |
| | - programmable acoustic brewing end signal loudness: loud, less loud, off |
| | - factory setting: loud |
| | - acoustic signals for push button feedback |
| | - acoustic signals for brew end signal |
| | - all acoustic signals are able to be switched on/off |
| Display | |
| | - Multi color graphic controlled matrix display with 240 dpi |
| Clock | |
| | - display of hours and minutes |
| | - white illumination on black background |
| Timer | |
| | - programmable start time |
| | - timer clock shown on display during setting |
| | - white LED indication, when activated |
| Automatic shut-off | |
| | - after brewing is finished |
| | - manual switch-off possible |
| ON-OFF-Switch | |
| | - automatic shut-off |
| | - manual switch-off possible |
| | - ON/OFF button |
| | - green LED indication |
| Power cord | |
| | - cord length 80 cm |
| | - storage in appliance |
| | - power cord outlet on the back |
| Approvals | |
| | - Safety approval (GS approval mark) |
| | - Food law approval |